

# Model : TM420

## 5" 4in1 Tester Monitor (Up to 2MP)



### Key Features

- Video Signal Testing : Compatible with AHD, TVI, CVI, CVBS video test, Up to 1080p Resolution
- 5.0 inch 800(RGB)x480 resolution. PAL/NTSC(Auto Adapt)
- PTZ Control: RS485 Control, Porter 1200~115200bps, compatible with PELCO-D/P protocol
- Image Generator: Multi-format video OUT port image generator, sending a variety of standard (e.g. PAL, NTSC) color graphics section
- Output DV 12V/1A Power out, supply temporarily power for the camera
- USB 2.0 interface provides 5V/1A emergency power output
- Audio signal input: Tester whether sound normal
- Enhanced UTP Cable/ BNC Cable Test, with indicator light, the test distance can reach 100-150 meters
- VGA input: VGA Support 1024\*768, 1289\*1024 resolution, VGA access need to enter the menu to select VGA mode
- Coaxial HD Test:
  - AHD Tester support 720P 25F/30F/50F/60F, 1080P 25F/30F.
  - TVI Tester support 720P 25F/30F/50F/60F, 1080P 25F/30F.
  - CVI Tester support 720P 25F/30F/50F/60F, 1080P 25F/30F.
- LED Emergency Lighting
- Built-in 3.7V Lithium polymer battery, 3000mAh
- Rechargeable: After charging 2-3 hour, working time lasts 6 hours
- Language: Chinese, English, Turkish, Russian, Japanese, Korean, French, Italian, Polish, German, Spanish, Portuguese
- General:
  - Working Temperature: 10°C- +50°C
  - Working Humidity: 30%-90%

# Model : TM420

5" 4in1 Tester Monitor (Up to 2MP)

## Device Diagram



### Package:

- 1x HD Coaxial Tester
- 1x Adapter DC5V 1.0A(With USB Cable)
- 1x BNC Cable
- 1x RS485 Connector
- 1x 12V Output Power Cable
- 1x Audio Cable
- 1x Wrist Band
- 1x User Manual
- 1x Tool Box

